

TYPE NO.: AOM440GF5C

- Full omni-directional radiation pattern
- DC-grounded (DC-short) - antistatic
- NO GROUNDPLANE NEEDED


ELECTRICAL SPECIFICATIONS:

FREQUENCY	430 - 450 MHz (TETRA or ISM)
IMPEDANCE	50 ohm
POLARISATION	Vertical
GAIN	3 dBd, 5.1 dBi
BANDWIDTH	20 MHz
VSWR	< 1.5
MAX. POWER	250 W

MECHANICAL SPECIFICATIONS:

COLOR	White
HEIGHT	Approx. 1440 mm
WEIGHT	500 g
MOUNTING	Attaches to a pole or wall (mounting kit + bracket is included)
MATERIALS	PU-painted heavy-duty Ø 18 mm glass-fibre tube and chrome plated brass
OPERATING TEMPERATURE	-40C to +70C
CONNECTOR 1	N-female
CABLE	No cable supplied
MOUNTING PLACE	On deck or mast etc.
INGRESS PROTECTION	IP66
ORDER NO.	AOM440GF5C

VERTICAL RADIATION PATTERN:



IKM Communication ApS
 Lyngvej 16, Building C
 Noerre Herlev
 DK3400 Hilleroed
 Denmark

Phone DK +45 2990 0919
 Phone SE +46 4104 3460
 e-mail sales@ikmcom.dk
 Website www.ikmcom.dk

CVR/VAT No. DK 36 05 76 88
 IBAN DK5030000011482724
 SWIFT DABADKK